

3 AA BATTERIES

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

XPP-5422GMA

**NIGHTSTICK**  
Life Depends on Light™



## DUAL-LIGHT

240-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation

IP-67  
DUST/WATER  
PROOF


HANDS-FREE  
INTEGRATED  
MAGNETS

ZONE 0

CLASS I  
DIV 1



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



**Powerful base magnet** allows "hands-free" use

CERTIFIED



240 LUMENS

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

**3 AA BATTERIES** (not included)

**ITEM NUMBER/UPC**

- XPP-5422GMA, UPC 0 1739880809 5

**MARKET APPLICATIONS**

- Hazardous work environments, industrial, fire and rescue

**CERTIFICATIONS**

- cETLus, ATEX, IECEx, CE, InMetro

**CASE MATERIAL**

- Engineered polymer

**LUMENS/RUNTIME**

**FLASHLIGHT**

-120L, 17.5 hrs. runtime

**FLOODLIGHT**

- 120L, 17.5 hrs. runtime

**DUAL-LIGHT**

- 240L, 4.5 hrs. runtime

**CANDELA**

- 7,250

**BEAM DISTANCE**

- 170 m

**WATER RATING**

- ANSI IP-67 dustproof / waterproof

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 7.0 in (178 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 6.9 oz (196 g)

**POWER SOURCE**







- AA batteries (not included)

**WARRANTY**

- Limited lifetime

**WHAT'S INCLUDED**

- Flashlight
- Removable lanyard
- Instruction manual

| FL 1 STANDARD  | SPOT       | FLOOD      | DUAL-LIGHT |
|--|------------|------------|------------|
|  | 120 LUMENS | 120 LUMENS | 240 LUMENS |
|  | 17h        | 17h        | 4h 30min   |
|  | 170m       |            |            |
|  | 7250cd     |            |            |
|  |            |            |            |
|  |            |            |            |

**Bayco Products, Inc. XPP-5422GMA**  
 640 S. Sanden Blvd.  
 Wylie, TX 75098



ID 4003544  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE



CLASS I DIV 1 GRPS A-D T3 Ex ia op is I Ma  
 CLASS II & III DIV 1 GRPS E-G T135C Ex ia op is IIC T3 Ga  
 CLASS I ZONE 0 AEx ia IIC T3 Ga Intertek ITS 13 ATEX27837X  
 CLASS I ZONE 0 Ex ia IIC T3 Ga IECEx ITS 16.0067X  
 Ⓢ I M 1 Ex ia op is I Ma -20°C ≤ Tamb ≤ +40°C  
 Ⓢ II 1 G Ex ia op is IIC T3 Ga 1.5V/Cell AA Alkaline

**Conforms to:**  
 ANSI/UL STD 913, ANSI/UL 60079-0,  
 ANSI/UL 60079-11 ANSI/ISA 60079-26

**Certified to:**  
 CAN/CSA STD C22.2 No 157  
 CAN/CSA STD C22.2 No 60079-0  
 CAN/CSA STD C22.2 No 60079-11  
 CSA STD C22.2 No 25

SEE INSTRUCTION MANUAL  
 VOIR MANUEL

MFG MM-YY

CERTIFIED



© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5422GMA-21

