

LI-ION RECHARGEABLE

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

XPR-5582RX

XPR-5582GX

NIGHTSTICK®

Life Depends on Light™

1750

POWERFUL LUMENS

INCLUDING HIGH & LOW



Rear green safety lights provide visibility in smoke filled applications



Carry strap with seat belt style buckle for additional hands-free use



Convenient locking snap-in charger included



Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment




180° DOWNWARD ROTATION



AVAILABLE IN MULTIPLE COLORS

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd



1750 LUMENS



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTEGRITAS™**LANTERN****LI-ION RECHARGEABLE****ITEM NUMBER/UPC**

XPR-5582RX (Red), UPC# 0 17398 806824
 XPR-5582GX (Green), UPC# 0 17398 807029

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position
 - US Patent 9,713,217

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 1750L, 5 hrs. runtime
 - LOW: 600L, 11 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 81,250
 - LOW: 27,083

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 552m
 - LOW: 325m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm
 - WIDTH: 4.26 in / 10.8 cm
 - DEPTH: 5.83 in / 14.8 cm
 - WEIGHT: 2 lbs. 11 oz. / 1219 g

BATTERY






- Rechargeable Li-ion battery pack

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Lantern
 - Li-ion rechargeable battery pack
 - Locking snap-in charger (5582-CHGR1)
 - AC power supply
 - DC direct wire kit with in-line fuse
 - Removable shoulder strap
 - Instruction manual

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
		



Bayco Products, Inc. XPR-5582
 640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 2 GRPS A-D T3
 CLASS II & III DIV 2 GRPS F-G T135°C
 CLASS I ZONE 2 Group IIC T3
 -20°C ≤ Tamb ≤ +40°C
 3.7V/Cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.
 AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.
 WARNING: Risk of ignition - Do not charge batteries in a hazardous area.
 AVERTISSEMENT: Danger d'inflammation - Ne pas charger les piles dans une zone dangereuse.

CERTIFIED



AVAILABLE IN MULTIPLE COLORS